

EisBaer EisTouch HI 6G – 10“ Touchpanel with PoE



Specification:

- Fanless Design, compact and maintenance free
- Intel® Celeron N2930 QuadCore 1.83GHz
- Intel® HD Graphic
- 4GB RAM
- 64 GB (M.2 SSD)
- OS: Windows 10 IoT
- 10,1“ Display 1280 x 800 Pixel
- Power supply: **PoE IEEE 802.3at** from 25Watt
- 1x USB 2.0 + 1x USB 3.0
- 1x Ethernet (10/100/1000MBit), 1x PoE-Ethernet
- 1x RS 232/422/485
- 1x internal speaker
- 1x Power supply via 12 VDC external
- Operational temperature: 0°C ~45°C
- Humidity: 0 ~ 90%, not condensing
- Size-Display (W x H x D): 263mm x 172 mm x 13mm
- Optional: EisTouch 6G - FM-wallbox (255 x 163 x 55 mm)
- Optional: EisTouch 6G - Mounting kit for hollow wall mounting
- Optional: EisTouch 6G – KNX-Interface
- Optional: EisTouch 6G - Cavity wall mounting kit
- Optional: EisBaer HI-Server 4.0 NT (Power supply)
- Optional: EisBaer Hardware license with 10 pages / 200 components/channel
- Optional: EisBaer Hardware license with 20 pages / 400 components/channel



Please note: The touch panel 6G does not have a microphone and therefore it can not be used as a door intercom indoor station.

Special surface-mounted frame made of stainless steel for replacing existing panels from third-party manufacturers. The flush-mounted housing of the previous touch panel can remain in place.

You can currently replace the following variants with our EisTouch 6G surface-mounted frame

- MT701
- Control Panel
- Comfort Panel
- Smart Panel



Existing flush-mounted housings



EisTouch 6G in surface mounting frame

Cut-out dimensions (flush-mounted housing - 10" EisTouch 6G):

Width: 255 mm (B) Height: 163 mm (A) Depth: 55 mm (C)
Surrounding support edge: 3mm per side



Optional accessories for flush-mounted housing - 10 "EisTouch 6G:

- Cavity wall mounting kit

